



ADVANCED FLUID  
MANAGEMENT SOLUTIONS

**RAASM S.p.a.**

Via Marangoni 33, 36022  
S. Zeno di Cassola (VI) Italy  
Tel. +39 0424 570891  
info@raasm.com

## P/N 1500830

Air operated pump s. C15F for oil with 20 kg reservoir (external  $\varnothing$  260÷330 mm), R 50:1 and air operated discharging valve

### AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Centralized lubrication, Shipping and offshore, Railway transport

### FEATURES

Flow rate	1330 cm <sup>3</sup> /min
Tank capacity	20 kg
Pressure ratio	50:1
Air inlet connection	G 1/4" (f)
Lubricant outlet connection	G 3/8" (f)
Working temperature	-25 ÷ +60 °C
Lubricant	oils > 40 cSt
Drum internal $\varnothing$	260 ÷ 330 mm
Pump(R 50:1)	p/n 62548
Drum cover	p/n 10/507
Membrane	-
Packing	No. 2 - 0,056 m <sup>3</sup>
Net weight	12 kg
Gross weight	12,7 kg



### OVERALL DIMENSIONS (mm)

