



ADVANCED FLUID  
MANAGEMENT SOLUTIONS

**RAASM S.p.a.**

Via Marangoni 33, 36022

S. Zeno di Cassola (VI) Italy

Tel. +39 0424 570891

info@raasm.com

## P/N 3085680

Air operated pump s. C30F for grease with 60 kg reservoir (internal  $\varnothing$  360÷400 mm), R 50:1 and delivery pressure control assembly

### AREAS OF USE

Aeronautics, Agriculture, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Centralized lubrication, Shipping and offshore, Railway transport

### FEATURES

Flow rate	1330 cm <sup>3</sup> /min
Tank capacity	60 kg
Pressure ratio	50:1
Air inlet connection	G 1/4" (f)
Lubricant outlet connection	G 3/8" (f)
Working temperature	-25 ÷ +60 °C
Lubricant	grease max NLGI 2
Drum internal $\varnothing$	360 ÷ 400 mm
Pump(R 50:1)	p/n 62174
Drum cover	p/n 10/532
Membrane	p/n 66400
Packing	No. 2 - 0,076 m <sup>3</sup>
Net weight	11,2 kg
Gross weight	11,8 kg



### OVERALL DIMENSIONS (mm)

